

[ PRODUCT SHEET ]

<b>Product:</b> Ascom d81
Shock proof and IP65 classified
Several alarm possibilities with location functionality
Centralized Management
Intrinsically safe for gas and dust environments
Multicast/Broadcast



## ASCOM d81 – A RELIABLE PARTNER IN DEMANDING SITUATIONS

The Ascom d81 handset is a unique combination of robustness and sophistication. A tough design coupled with an outstanding level of functionality and operating safety make it the natural choice for users demanding operational excellence in the most challenging settings, such as industrial plants and secure establishments.

### Designed to be challenged

The d81 can be relied on in the toughest working environments, where the handset is handled roughly and is exposed to the elements. Not only does it resist rain, humidity and dust, but the strong rubber casing protects the handset if dropped. It is tested for twice the standard level of static electricity and it endures both cold and heat. There is also an intrinsically safe variant for operation in hazardous locations.

### Individuality meets functionality

Based on a proven IP-DECT operating platform with high volume and voice quality, the functionality of the d81 can be matched to the specific needs of your organization and the individuals in it. The advanced messaging functionality of the d81 means smooth interaction with colleagues or machinery. For example, information from production processes can be sent directly to the handset. Thanks to Centralized Management, the handsets in the system can be automatically configured, upgraded and updated. Furthermore, the functionality of the d81 can be complimented through the application of a number of additional licenses.

### Confidence through a high level of safety

The advanced alarm functions include a manual alarm and an automatic man-down and no-movement alarm. Dual functionality lets the user make a call and send an alarm at the same time. The person sending the alarm can be pinpointed with high accuracy and the messages can be automatically sent to the handsets in closest proximity to any reported event. In short, the d81 can make a major contribution to minimizing safety risks.

PRODUCT SHEET: d81

Ascom d81 Features at a glance		
<ul style="list-style-type: none"> <li>IP65, including headset and charging connector</li> <li>Shock proof</li> <li>Temperature range -10°C to +55°C, Ex -10°C to +40°C</li> <li>ATEX and IECx approved, CSA listed</li> <li>Intrinsically safe (Ex) for both gas and dust environments</li> </ul>	<ul style="list-style-type: none"> <li>Alarms: push-button, man-down, no-movement and pull-cord</li> <li>Location technologies: base-station, DECT location and LF</li> <li>Location functions: poll location and special location</li> <li>Bluetooth bar code reader license</li> </ul>	<ul style="list-style-type: none"> <li>Shared phone license</li> <li>Upgrade license from Messenger to Protector</li> <li>Centralized Management</li> <li>Color coded messages</li> <li>Message priority</li> </ul>

d81 Variant feature comparison						
	d81 Messenger	d81 Messenger LF	d81 Messenger Ex	d81 Protector	d81 Protector LF	d81 Protector Ex
Advanced messaging	✓	✓	✓	✓	✓	✓
Location	✓	✓	✓	✓	✓	✓
Bluetooth	✓	✓	✓	✓	✓	✓
Push-button alarm				✓	✓	✓
Man-down, no-movement and pull-cord alarm				✓	✓	✓

d81 Technical specifications		
<b>Dimensions</b> 142x56x25mm. <b>Weight</b> (incl. battery & clip) 170g. <b>Display</b> (CSTN) 28x35mm.	<b>Languages</b> 18: Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese (Brazilian), Russian, Slovakian, Spanish, Swedish, Turkish, + 1 downloadable.	<b>Connectors</b> Multi-purpose, IP65 classified connector for headset, battery charging, software download and configuration.
<b>Compliance</b> Compliance to EU, US, Canadian, Australian and Russian standards – please see the data sheet.		<b>Personal alarm</b> Push-button alarm, man-down alarm, no-movement alarm and pull-cord alarm.
<b>Battery</b> Type: Li-Ion. Speech time: up to 18 hrs, 12 hrs (with bluetooth headset). Stand-by time: up to 120 hrs <sup>1</sup> . Charge time: 3 hrs. Discharge/charge cycles: >=80% capacity left after 400 full charge/discharge cycles.	<b>Phonebook</b> Central phonebook: Unlimited no. of entries. Company phonebook: 1000 entries. Local phonebook: 250 entries.	<b>User Interface</b> High resolution backlit color display. Indicator: LED indicates incoming call/message. Vibration: Incoming call/message. Buttons & Keys: 3 Soft keys, off-hook key, on-hook and power on/off on the same key, 4 way navigation key, numerical keys, volume up/down and alarm button.
	<b>Intrinsically Safe</b> (Ex classification) <sup>3,4</sup> ATEX approved and IECEx approved. CSA listed for North America.	
<b>Audio</b> Ring signal: Adjustable in 8 steps. Earpiece: Adjustable in 8 steps of 3dB each. Max. sound ring signal level: 100 dBspl (90 dBspl for Ex) @ 10 cm. Loudspeaker: Duplex loud speaking function.	<b>Telephony</b> Indication: 14 ring signals, flashing LED, vibration. Answer call: Button press or auto answer. Call list storage capacity: 25 received, dialed and missed calls, with time stamp.	<b>Messaging</b> Storage capacity: Up to 20,000 characters, 30 received/sent messages. Messages from handset to handset 160 characters.
<b>Radio</b> DECT protocol detection: Automatic detection and configuration for US DECT and EU DECT at initial registration. Frequency range: EU (1880-1900 MHz), US (1920-1930 MHz), L A (1910-1930 MHz), BR (1910-1920 MHz), Other (1900-1920 MHz). Antenna: Integral. Radiated power: EU/L A/BR (250 mW), US (100 mW)	<b>Accessories</b> Add on licenses: Shared phone, bluetooth data and DECT location. Upgrade licenses: Protector and pull-cord. Desktop chargers (basic and advanced). Charging rack and battery pack charging rack. Headsets: microphone on boom and Peltor hearing protection headset. Clips (swivel, hinge). Front plates in several colors.	<b>Environmental</b> Operating temperature: -10°C to +55°C (-10°C to +40°C for Ex). Storage temperature <sup>2</sup> : -20°C to +60°C. Enclosure protection: IP65, IEC EN60529. Immunity to ESD: 8 kV contact discharge, 16 kV air discharge (EN61000-4-2). Free fall test, standard product: IEC 60068-2-32, procedure 1, dropped 12 times, specification extended to 2 meters. IEC 68-2-32, procedure 2, dropped 1,000 times from 0.5 meter.
<b>Bluetooth</b> Supports handsfree and headset profiles. See data sheet for tested headsets. License for barcode scanners.	<b>Location</b> Basestation location as standard, LF location as factory option and DECT location as license.	

<sup>1</sup> Stand-by time is without activated screensaver. <sup>2</sup> Storing Li-Ion batteries at high temperatures can dramatically and permanently reduce capacity.

<sup>3</sup> Disclaimer: Explosive atmosphere; The approvals are valid exclusively for surface industry. Ascom explosion protected d81 handset shall therefore not be used in mining (underground) location. Ascom Sweden AB does not support or take responsibility for any change in the product or its designation.

<sup>4</sup> In EX classified areas; it is NOT permitted to charge the battery while it is in the intrinsically safe ATEX/IECEx telephone, remove the battery, or charge it separately.

Ascom Wireless Solutions

P.O. Box 8783 SE-402 76 Göteborg, Sweden  
 T +46 31 55 93 00 | F +46 31 55 20 31  
[www.ascom.com](http://www.ascom.com)